

MODUL 3000 Replacement Kit



H: 120 mm, W: 200 mm, L: 200 mm

General specifications

| | |
|----------------------------|--|
| Enclosure | Cover made of flat toughened safety glass, flush-mounted and screwed into the housing; weather-resistant |
| Rated luminous flux | 1.485 lm - 5.153 lm, L90/B10 for 100.000 h |
| Light colour | 4.000 K, 3.000 K, 2.700 K, 1.800 K, others on request |
| Rated input power | 11 W - 37W |
| Protection rating | I or II |
| Surface vulnerable to wind | Depending on luminaire installation type |
| Weight | approx. 2 kg resp. 2,7 kg |
| Finish | Housing aluminum untreated, cover round standard white, further colors upon request |
| Optics | Pages 24 - 26 |

Additional specifications


| | |
|---|--|
| Housing | Aluminium die cast |
| Installation | Cover round is adapted to housing type; diameter variable |
| Light regulation (optional with dimming function) | Constant Lumen Management (CLM); autonomous performance reduction for operation in networks without a control line (Light Regulation Autarkic – LRA); performance reduction by switching off a control line (Light Regulation Twin – LRT); deliverable with Zhaga Book 18 socket |

IP rating depending on luminaire application.



Multifunctional installation kit

- ✓ Conversion kit for outdoor luminaire types such as Cylinder lights, bell lights and umbrella lights, heritage lights and technical street lights
- ✓ The cover crown required for fastening is adapted to the specific design of the type
- ✓ Conversion kit also possible for third-party lights
- ✓ Best for pole heights from 4m up to 8m



Find more technical details
<https://www.vulkan.eu/en/decorative-lighting/module-3000/>